

# NON-GASTRONORM

## Undercounter: Solid Door Refrigerators



HABS solid door undercounters are finished in 304 stainless steel. Features include: fan forced ducted cooling, Carel electronic controller, Danfoss compressor, adjustable wire shelving, coved internal corners, removable door seals, stainless steel work top, and come standard with lockable castors overall height 835mm high.

Model Number	MGCR120S	MGCR150S	MGCR180S-2/3
External W x D x H (mm) (with legs)	1200 x 600 x 850	1500 x 600 x 850	1800 x 600 x 850
Internal W x D x H (mm)	800 x 590 x 550mm	1100 x 590 x 550	1400 x 590 x 550
Nett Capacity (ltr)	210	260	455
Shelves	2	2	2
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ	220 - 240V 50HZ
Compressor	Danfoss	Danfoss	Danfoss
Weight Empty (kg)	90	118	138
Max. Power Consumption Watt	325w	375w	385w
Temperature Range (°C)	+2/+4	+2/+4	+2/+4
Refrigerant Gas	R134a	R134a	R134a
Insulation Gas	CFC free	CFC free	CFC free
Insulation Thickness (mm)	50	50	50
Max. Ambient Temp (°C) 75RH	43	43	43
Exterior Material	S/S AISI304	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304	S/S AISI304

### Options

S/S Top fitted with splash back at 150mm

Extra Shelf & Clips

150mm Legs

# NON-GASTRONORM

## Undercounter: Solid Door Refrigerators



MGCR210S



MGCR240S



Removable cold unit

HABS solid door undercounters are finished in 304 stainless steel. Features include: fan forced ducted cooling, Carel electronic controller, Danfoss compressor, adjustable wire shelving, coved internal corners, removable door seals, stainless steel work top, and come standard with lockable castors overall height 835mm high.

NON-GASTRONORM

Model Number	MGCR210S-3	MGCR240S-3
External W x D x H (mm) (with legs)	2100 x 600 x 850	2400 x 600 x 850
Internal W x D x H (mm)	1640 x 440 x 550	1910 x 440 x 550
Nett Capacity (ltr)	440	575
Shelves	3	3
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ
Compressor	Danfoss	Danfoss
Weight Empty (kg)	145	180
Max. Power Consumption Watt	480w	515w
Temperature Range (°C)	+2/+4	+2/+4
Refrigerant Gas	R134a	R134a
Insulation Gas	CFC free	CFC free
Insulation Thickness (mm) 90mm top	50	50
Max. Ambient Temp (°C)	43	43
Exterior Material	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304

### Options

S/S Top fitted with splash back at 150mm

Extra Shelf & Clips

150mm Legs

# NON-GASTRONORM

## Undercounter: Glass Door Refrigerators



MGCR120-GD-WL



MGCR240-GD-WL

HABS non-gastronorm glass door refrigerator undercounters are finished in 304 stainless steel. Features include: fan forced ducted cooling, Carel electronic controller, adjustable wire shelving, coved internal corners and double glazed doors with removable door seals, S/S work top and come standard with lockable castor. Overall height 835mm

Model Number	MGCR120-GD	MGCR150-GD	MGCR180-GD	MGCR210-GD	MGCR240-GD
External W x D x H (mm) (with legs)	1200 x 600 x 850	1500 x 600 x 850	1800 x 600 x 850	2100 x 600 x 850	2400 x 600 x 850
Internal W x D x H (mm)	800 x 590 x 550	1100 x 590 x 550	1400 x 590 x 550	1640 x 590 x 550	1910 x 590 x 550
Nett Capacity (ltr)	210	260	455	535	625
Shelves	2	2	2	3	3
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ	220 - 240V 50HZ	220 - 240V 50HZ	220 - 240V 50HZ
Compressor Size	Danfoss	Danfoss	Danfoss	Danfoss	Danfoss
Weight Empty (kg)	90	118	138	154	183
Max. Power Consumption Watt	495w	565w	585w	640w	695w
Temperature Range (°C)	+2/+4	+2/+4	+2/+4	+2/+4	+2/+4
Refrigerant Gas	R134a	R134a	R134a	R134a	R134a
Insulation Gas	CFC free	CFC free	CFC free	CFC free	CFC free
Insulation Thickness (mm)	60	60	60	60	60
Max. Ambient Temp (°C) 75RH	36	36	36	36	36
Exterior Material	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304

### Options

S/S Top fitted with splash back at 150mm

Extra Shelf with Clips

150mm Legs

# NON-GASTRONORM

## Undercounter: Solid Door Refrigerator/Freezer



HBSRNX200  
Shown with glass door option



HBSRCX200

These single solid/glass door cabinets are ideal for the storage of food product in your commercial applications. They are fitted with controlled temperature displays, door locks, baskets and finished in a 304 stainless steel exterior. Cabinets can be easily fitted under benches for convenience.

NON-GASTRONORM

Model Number	HBSRNX200	HBSRCX200
Packing dimension (mm)	640 x 680 x 880	640 x 680 x 880
External W x D x H (mm)	600 x 660 x 840	600 x 660 x 840
Internal W x D x H (mm)	490 x 440 x 620	490 x 440 x 620
Interior Volume	185L	185L
Temperature Range (°C)	-10 / -20	2/+5
Refrigerant Gas	R134a	R134a
Foaming material	Cyclopentane	Cyclopentane
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ
Compressor	Zanussi	Zanussi
Exterior colour	S/S	S/S
Interior color	White	White
Door color	Solid	Solid
Lock	Yes	Yes
Shelve quantity	2pcs	2pcs
Thermostat	Digital	Digital
Temperature display digital	Yes	Yes
Length of power cord	1.5m	1.5m
Gross weight (App)	46kg	46kg
Container quantity 20'	54	54
Container quantity 40'	108	108
Container quantity 40' HQ	162	162

# NON-GASTRONORM

## Upright: Solid Half-Door Refrigerators



The HABS non-gastronorm solid half-door upright refrigerators are finished in 304 stainless steel. Features include: fan forced ducted cooling, Carel electronic controller, adjustable wire shelving, coved internal corners with removable door seals, and standard with lockable castors 135mm.

Model Number	MGUR60	MGUR120	MGUR180
External W x D x H (mm) (includes castors)	600 x 740 x 1940	1200 x 740 x 1940	1800 x 740 x 1940
Internal W x D x H (mm)	480 x 580 x 1405	1080 x 580 x 1405	1680 x 580 x 1405
Nett Capacity (ltr)	425	955	1485
Shelves	3	6	9
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ	220 - 240V 50HZ
Compressor	Danfoss	Danfoss	Danfoss
Weight Empty (kg)	134	150	185
Max. Power Consumption Watt	460w	600w	850w
Temperature Range (°C)	+2/+4	+2/+4	+2/+4
Refrigerant Gas	R134a	R134a	R134a
Max. Ambient Temp (°C) 75RH	40	40	40
Insulation Gas	CFC free	CFC free	CFC free
Insulation Thickness (mm)	60	60	60
Exterior Material	S/S AISI304	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304	S/S AISI304

### Options

Extra Shelf & Clips

150mm Legs

# NON-GASTRONORM

## Upright: Solid Half-Door Freezers



Our non-gastronorm solid half-door upright freezers are finished in 304 stainless steel. Features include: fan forced ducted cooling, Carel electronic controller, adjustable wire shelving, coved internal corners with removable door seals and come standard with lockable castors 135mm and heated facias.

NON-GASTRONORM

Model Number	MGUF60	MGUF120	MGUF180
External W x D x H (mm) (includes castors)	600 x 740 x 1940	1200 x 740 x 1940	1800 x 740 x 1940
Internal W x D x H (mm)	480 x 580 x 1405	1080 x 580 x 1405	1680 x 580 x 1405
Nett Capacity (litr)	410	955	1485
Shelves	3	6	9
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ	220 - 240V 50HZ
Compressor	Danfoss	Danfoss	Danfoss
Weight Empty (kg)	113	160	220
Max. Power Consumption Watt	720w	850w	1350w
Temperature Range (°C)	-14/-20	-14/-20	-14/-20
Refrigerant Gas	R404a	R404a	R404a
Max. Ambient Temp (°C)	40	40	40
Insulation Gas	CFC free	CFC free	CFC free
Insulation Thickness (mm)	60	60	60
Exterior Material	S/S AISI304	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304	S/S AISI304

### Options

Extra Shelf & Clips

150mm Legs

# NON-GASTRONORM

## Upright: Glass Door Refrigerators



MGUR70GD



MGUR140GD

HABS non-gastronorm glass door upright refrigerators are finished in 304 stainless steel.

Features include: fan forced ducted cooling, Carel electronic controller, adjustable wire shelving, coved internal corners with removable door seals and come standard with lockable castors 135mm.

Model Number	MGUR70GD	MGUR140GD
External W x D x H (mm) (with castors)	702 x 805 x 2028	1398 x 805 x 2028
Door Open Depth (mm)	1449	1449
Internal W x D x H (mm)	587 x 690 x 1518	1280 x 690 x 1518
Nett Capacity (ltr)	615	1340
Shelves	3	6
Voltage Hertz	220 - 240V 50HZ	220 - 240V 50HZ
Compressor	Danfoss	Danfoss
Weight Empty (kg)	147	226
Max. Power Consumption Watt	505w	580w
Temperature Range (°C)	+2/+4	+2/+4
LED Lighting	1	2
Refrigerant Gas	R134a	R134a
Insulation Gas	CFC free	CFC free
Insulation Thickness (mm) 90mm top	60	60
Max. Ambient Temp (°C)	36	36
Exterior Material	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304

### Options

Extra Shelf & Clips

150mm Legs